

## Swing Hoist HydraPaks

RGC® HydraPaks are portable, lightweight power sources that put reliable, efficient hydraulic power at your Swing Hoist job site. They are easily transported to the job site in the back of a pick up truck or van.

HydraPaks are cart-mounted, equipped with a lifting eye, 16 in. pneumatic tires and are available in gas and electric models. Each gas unit has low oil engine shutdown, a heavy-duty heat exchanger and 6 gallon hydraulic reservoir.



HV1658S HydraPak

## Hoisting HydraPaks Features & Benefits

- ▶ Compact, lightweight portable hydraulic power source for RGC Swing Hoists.
- ▶ Cart-mounted with large 16 in. pneumatic tires for easy transporting.
- ▶ Low noise level.
- ▶ Easy maintenance and parts replacement.
- ▶ Electric start and low oil shutdown on oil gas models.
- ▶ Controls easily accessible for safety and comfort.
- ▶ Powder-coated tubular steel frame protects unit from damage.
- ▶ Detachable handles for easy transporting and storage.
- ▶ 12V battery included on all models.
- ▶ Lifting eye and 6 gallon oil reservoir.
- ▶ Heavy duty 8-tube heat exchanger on most models.
- ▶ The HV1858S is equipped with an 18 hp B&S Vanguard gas engine with electronic governor.
- ▶ Five models are now equipped with a safety valve to power Swing Hoists with the Limit Switch Accessory.

## Swing Hoist HydraPak Specifications

Model	H1058S	HH1158S	HH1358S	HV1658S	HV1858S	HE7558S
<b>Engine</b>	B&S 10 hp	Honda 11 hp	Honda 13 hp	B&S 16 hp Vanguard V-Twin	B&S 18 hp Vanguard V-Twin w/ Auto Idle	Baldor 7-1/2 hp 3 ph electric motor
<b>Flow</b>	5 or 8 gpm (20 or 30 lpm)	5 or 8 gpm (20 or 30 lpm)	5 or 8 gpm (20 or 30 lpm)	5 or 8 gpm (20 or 30 lpm)	5 or 8 gpm (20 or 30 lpm)	5 or 8 gpm (20 or 30 lpm)
<b>Operating Pressure (Max)</b>	2000 psi (138 bar)	2000 psi (138 bar)	2250 psi (155 bar)	2500 psi (172 bar)	2250 psi (155 bar)	2000 psi (138 bar)
<b>Hour Meter</b>	Yes	Yes	Yes	Yes	Yes	Yes
<b>Pull Start</b>	Yes	Yes	Yes	Yes	Yes	Yes
<b>Electric Start</b>	Yes	Yes	Yes	Yes	Yes	Yes
<b>Winch &amp; Boom Valves</b>	Yes	Yes	Yes	Yes	Yes	Yes
<b>Weight</b>	195 lbs. (139 kg)	195 lbs. (134 kg)	240 lbs. (109 kg)	280 lbs. (227 kg)	220 lbs. (120 kg)	326 lbs. (148 kg)
<b>Safety Valve for Limit Switch</b>	No	Optional	Optional	Optional	Optional	Optional