

The Superior Air - Jacketed Hot Rubber Melters
(Propane, Diesel, & Electric Heat Systems Available)

From the Innovators of Rubber Master Technology



A-60



As with our A110, the A60 is easily accommodated in commercial elevators, it fits through standard 34" doorways and comes equipped with optional casters for easy movement. Pump system also available with gas or electric drive. Material ready in less than 30 minutes

Our new A-60 Melter is one step above our 40 gallon melter. It's perfect for those in between jobs with the efficiency to match our larger melters.



Also Available: We have our optional custom A-60 trailer mount for easy transport on the back of existing trailers.



Shown with optional diesel burner

The Superior Air-Jacketed Hot Rubber Melter

From the Innovators of Rubber Master Technology

A-60



SPECIFICATIONS: A- 60 (60 US gallon capacity)

Heat Transfer Oil	None Required	Fire tube.....	4" Sch 80 Stainless steel
Capacity (Custom Sizes Available)	60 US Gallons		
Agitator	Honda 4.0 H.P. Gas, 110V Electric or Optional 6.0 HP Diesel Motor		
Overall Dimensions (Melter only)	L-59" W-33 5/8" H-45"		
Burner.....	Adjustable Liquid Propane 1 X 500,000 BTU or Optional Beckett Diesel Burners		
Temperature Controls	Optional		
Inner Shell	3/16" Rolled Steel		
Outer Shell	1/8" Rolled Steel		
Insulated Jacket	1/2" super high temp plus 2" High Temp. Fiberglass		
Shipping Weight (Melter only)	1250 lbs.		
Optional Trailer (with melter mounted).....	L-144" x W-58" x H-66" 1,525 lbs.		
Suspension 4" Drop Axle	3500 lb. Axle and Springs		
Tires	2 X 6.00 X 14"		
Trailer Chassis	4" Steel Channel		
Brakes	Optional		
Tow Hitch	As ordered c/w safety chain		
Pump	Optional 1 1/2" Viking		
Horizontal Wand Pumping System	Optional		

Heated Material Output:

- material capacity: 60 US gallons	60 gal./50 hr x 78.9 % = 94.7 gal./hr
- heat up time: 30 min's (0.50 hr.)	358.4 L /50 hr x 78.9 % = 565.5 L /hr
- efficiency: 78.9%	