

GUARDIAN

FALL PROTECTION



Product Name: SkyMast Skyhook

Part #: 00305; 00315; 00325; 00335; 00345

Instruction Manual

Do not throw away these instructions!
Read and understand these instructions before using equipment!

Introduction	1
Applicable Safety Standards	1
Worker Classifications	1
Product Specific Applications	1-2
Limitations	2-3
Components and Specifications	3
Installation and Use	4
Maintenance, Cleaning, and Storage	5
Inspection	5
Inspection Log	5
Safety Information	6
Labels	7

Introduction

Thank you for purchasing a Guardian Fall Protection SkyMast Skyhook. This manual must be read and understood in its entirety, and used as part of an employee training program as required by OSHA or any applicable state agency.


This and any other included instructions must be made available to the user of the equipment. The user must understand how to safely and effectively use the SkyMast Skyhook, and all fall safety equipment used in combination with the SkyMast Skyhook.

User Information	
Date of First Use:	_____
Serial #:	_____
Trainer:	_____
User:	_____

Applicable Safety Standards

When used according to instruction specifications, this product meets or exceeds all applicable OSHA 1926 Subpart M, OSHA 1910, ANSI Z359.1-2007, and ANSI A10.32-2012 standards for fall protection. Applicable standards and regulations depend on the type of work being done, and also might include state-specific regulations. Consult regulatory agencies for more information on personal fall arrest systems and associated components.

Worker Classifications

 CAUTION	Understand the following definitions of those who work near or who may be exposed to fall hazards.
--	--


Qualified Person: A person with an accredited degree or certification, and with extensive experience or sufficient professional standing, who is considered proficient in planning and reviewing the conformity of fall protection and rescue systems.

Competent Person: A highly trained and experienced person who is ASSIGNED BY THE EMPLOYER to be responsible for all elements of a fall safety program, including, but not limited to, its regulation, management, and application. A person who is proficient in identifying existing and predictable fall hazards, and who has the authority to stop work in order to eliminate hazards.

Authorized Person: A person who is assigned by their employer to work around or be subject to potential or existing fall hazards.

It is the responsibility of a Qualified or Competent person to supervise the job site and ensure all applicable safety regulations are complied with.

Product Specific Applications

 WARNING	Use of equipment in unintended applications may result in serious injury or death. Maximum 1 attachment per connection point.
---	---



Personal Fall Arrest: SkyMast Skyhook may be used to support a MAXIMUM 1 PFAS for use in Fall Arrest applications. Structure must withstand loads applied in the directions permitted by the system of at least 5,000 lbs. Maximum free fall is 6', or up to 12' if used in combination with equipment explicitly certified for such use. Applicable D-ring: Dorsal.



Restraint: SkyMast Skyhook may be used in Restraint applications. Restraint systems prevent workers from reaching the leading edge of a fall hazard. Always account for fully deployed length of lanyard/SRL. Structure must withstand loads applied in the directions permitted by the system of at least 1,000 lbs. No free fall is permitted. Restraint systems may only be used on surfaces with slopes up to 4/12 (vertical/horizontal). Applicable D-rings: Dorsal, Chest, Side, Shoulder.



Work Positioning: SkyMast Skyhook may be used in Work Positioning applications. Work Positioning systems allow a worker to be supported while in suspension and work freely with both hands. Structure must withstand loads applied in the directions permitted by the system of at least 3,000 lbs. Maximum allowable free fall is 2'. Applicable D-rings: Side, Shoulder.


For all applications: worker weight capacity range (including all clothing, tools, and equipment) is 130-420 lbs.

Limitations

Fall Clearance: There must be sufficient clearance below the anchorage connector to arrest a fall before the user strikes the ground or an obstruction. When calculating fall clearance, account for a MINIMUM 3' safety factor, deceleration distance, user height, length of lanyard/SRL, and all other applicable factors.

Diagram shown is an example fall clearance calculation ONLY.

Swing Falls: Prior to installation or use, make considerations for eliminating or minimizing all swing fall hazards. Swing falls occur when the anchor is not directly above the location where a fall occurs. Always work as close to in line with the anchor point as possible. Swing falls significantly increase the likelihood of serious injury or death in the event of a fall.



Compatibility: When making connections with SkyMast Skyhook, eliminate all possibility of roll-out. Roll-out occurs when interference between a hook and the attachment point causes the hook gate to unintentionally open and release. All connections must be selected and deemed compatible with SkyMast Skyhook by a Competent Person. All connector gates must be self-closing and self-locking, and withstand minimum loads of 3,600 lbs. See the following for examples of compatible/incompatible connections:

Connector closed and locked to D-ring. **OK.**



Connector to integral lanyard. **NO.**

Two or more snap hooks or carabiners connected to each other. **NO.**



Connector directly to webbing. **NO.**

Two connectors to same D-ring. **NO.**



Application that places load on gate. **NO.**

Incompatible or irregular application, which may increase risk of roll-out. **NO.**




Connector directly to horizontal lifeline. **NO.**

Correct Anchorage Positioning:

This chart details allowable working zones required to reduce risk of swing falls and improper side loading. ALWAYS adhere to information specified by chart.

Anchor Distance From Leading Edge (Y)	Working Distance Along Roof Edge (Either Direction) (X)	Working Angle From Perpendicular (θ)
6'	8'	53°
10'	9' - 9"	45°
15'	11' - 7"	38°
20'	13' - 3"	33°
25'	14' - 6"	30°
30'	16'	28°
35'	17' - 2"	26°
40'	18' - 3"	24°
45'	19' - 4"	23°
50'	19' - 10"	21°
55'	21' - 4"	21°
60'	22' - 3"	21°



For example, if the anchorage connector is 6' from the leading edge (Y), the working distance (X) is 8' in each direction from the perpendicular, which translates to a 53° working angle.

Components and Specifications

Materials: powder-coated steel.

Part #	Weight	Description
00305	14 lbs.	SkyMast Skyhook. Applicable roof pitch: flat.
00315	14 lbs.	SkyMast Skyhook. Applicable roof pitch: 1/12 - 3/12.
00325	14 lbs.	SkyMast Skyhook. Applicable roof pitch: 4/12 - 6/12.
00335	14 lbs.	SkyMast Skyhook. Applicable roof pitch: 7/12 - 9/12.
00345	14 lbs.	SkyMast Skyhook. Applicable roof pitch: 10/12 - 12/12.



Installation and Use

Prior to installation, plan your system:

1. PFAS equipment must be selected and deemed compatible with SkyMast Skyhook by a Competent Person.
2. Eliminate or minimize all risk of swing fall.
3. Determine desired installation location for SkyMast Skyhook; ensure location is free of debris, rot, decay, cracking, and hazardous materials. NEVER install on gable ends, fascias, rake ends, overhangs, bottom cords, collar boards, spliced sections, or substrate incapable of withstanding application minimum loads.

Installation:

MINIMUM substrate requirements:

Wood: 3/4" CDX or better. Metal: 20g or thicker. Concrete: 2,000 p.s.i. or better.
Skyhook Anchor MUST install flush against substrate.


Skyhook Anchors MUST be placed a MINIMUM 10' from all leading edges of fall hazards.
Installation MUST be supervised by a Competent Person.

1. Place Skyhook Anchor over selected roof ridge. Skyhook Anchor must lie flush with substrate.
2. Ensure all fasteners are those supplied by Guardian Fall Protection, or are deemed compatible by a Competent Person.
3. For installations on wood and metal, use 18 total (9 per side) #14x10 2" screws. To avoid possibility of splitting roof truss, do not install fasteners directly in line with each other. NEVER use nails.
4. For installation on concrete, use (18 total, 9 per side) concrete fasteners. Fasteners MUST be selected and deemed compatible with SkyMast Skyhook by a Competent Person.

- Wood/Metal installation: Install fasteners according to image. In wood applications, all fasteners MUST be installed into roof truss or other compatible support beam.

- Concrete installation: Install fasteners according to image. Installation must be done directly on substrate, and never through any intermediary substrates.

5. Connect complete and compatible PFAS to SkyMast Skyhook Connection Point, OR install SkyMast Anchor (part # 00271) according to product instructions.



On each side, install fasteners in locations indicated on image. Other fastener layouts may be used if deemed acceptable by a Competent Person.

Maintenance, Cleaning, and Storage

If SkyMast Skyhook fails inspection in any way, immediately remove it from service, and contact Guardian to inquire about its return or repair.

Cleaning after use is important for maintaining the safety and longevity of SkyMast Skyhook. Remove all dirt, corrosives, and contaminants from SkyMast Skyhook before and after each use. If SkyMast Skyhook cannot be cleaned with plain water, use mild soap and water, then rinse and wipe dry. NEVER clean SkyMast Skyhook with corrosive substances.

When not in use, store equipment where it will not be affected by heat, light, excessive moisture, chemicals, or other degrading elements.

Inspection

Prior to EACH use, inspect SkyMast Skyhook for deficiencies, including, but not limited to, corrosion, deformation, pits, burrs, rough surfaces, sharp edges, cracking, rust, paint buildup, excessive heating, alteration, and missing or illegible labels. IMMEDIATELY remove SkyMast Skyhook from service if defects or damage are found, or if exposed to forces of fall arrest.

Ensure that applicable work area is free of all damage, including, but not limited to, debris, rot, rust, decay, cracking, and hazardous materials. Ensure that selected work area will support the application-specific minimum loads set forth in this instruction manual. Work area MUST be stable.

At least every 6 months, a Competent Person other than the user must inspect SkyMast Skyhook. **Competent Person inspections MUST be recorded in inspection log in instruction manual and on equipment inspection grid label. The Competent Person must sign their initials in the box corresponding to the month and year the inspection took place.**

During inspection, consider all applications and hazards SkyMast Skyhook have been subjected to.

Inspection Log

Date of First Use: _____.

Product lifetime is indefinite as long as it passes pre-use and Competent Person inspections. User must inspect prior to EACH use. Competent Person other than user must complete formal inspection at least every 6 months. Competent Person to inspect and initial.

This inspection log must be specific to one SkyMast Skyhook. Separate inspection logs must be used for each SkyMast Skyhook. All inspection records must be made visible and available to all users at all times.

	J	F	M	A	M	J	J	A	S	O	N	D
YR												
YR												
YR												
YR												
YR												

If equipment fails inspection IMMEDIATELY REMOVE FROM SERVICE.

Safety Information



Failure to understand and comply with safety regulations may result in serious injury or death. Regulations included herein are not all-inclusive, are for reference only, and are not intended to replace a Competent Person's judgment or knowledge of federal or state standards.

Do not alter equipment. Do not misuse equipment.

Workplace conditions, including, but not limited to, flame, corrosive chemicals, electrical shock, sharp objects, machinery, abrasive substances, weather conditions, and uneven surfaces, must be assessed by a Competent Person before fall protection equipment is selected.

The analysis of the workplace must anticipate where workers will be performing their duties, the routes they will take to reach their work, and the potential and existing fall hazards they may be exposed to. Fall protection equipment must be chosen by a Competent Person. Selections must account for all potential hazardous workplace conditions. All fall protection equipment should be purchased new and in an unused condition.

Fall protection systems must be selected and installed under the supervision of a Competent Person, and used in a compliant manner. Fall protection systems must be designed in a manner compliant with all federal, state, and safety regulations. Forces applied to anchors must be calculated by a Competent Person.

Unless explicitly stated otherwise, the maximum allowable free fall distance for lanyards must not exceed 6'. No free fall allowed for non-LE SRLs. Class A SRLs must arrest falls within 24"; Class B SRLs must arrest falls within 54".

Harnesses and connectors selected must be compliant with manufacturer's instructions, and must be of compatible size and configuration. Snap hooks, carabiners, and other connectors must be selected and applied in a compatible fashion. All risk of disengagement must be eliminated. All snap hooks and carabiners must be self-locking and self-closing, and must never be connected to each other.

A pre-planned rescue procedure in the case of a fall is required. The rescue plan must be project-specific. The rescue plan must allow for employees to rescue themselves, or provide an alternative means for their prompt rescue. Store rescue equipment in an easily accessible and clearly marked area.

Training of Authorized Persons to correctly erect, disassemble, inspect, maintain, store, and use equipment must be provided by a Competent Person. Training must include the ability to recognize fall hazards, minimize the likelihood of fall hazards, and the correct use of personal fall arrest systems.

NEVER use fall protection equipment of any kind to hang, lift, support, or hoist tools or equipment, unless explicitly certified for such use.

Equipment subjected to forces of fall arrest must immediately be removed from use.

Age, fitness, and health conditions can seriously affect the worker should a fall occur. Consult a doctor if there is any reason to doubt a user's ability to withstand and safely absorb fall arrest forces or perform set-up of equipment. Pregnant women and minors must not use this equipment.

Physical harm may still occur even if fall safety equipment functions correctly. Sustained post-fall suspension may result in serious injury or death. Use trauma relief straps to reduce the effects of suspension trauma.

Labels

GUARDIAN
FALL PROTECTION
SkyMast Skyhook Anchor
Part #: 00305
Date of manufacture: [REDACTED]

Prior to use, read and understand all instructions provided with equipment at time of shipment from manufacturer.

Compliant with all OSHA 1910, OSHA 1926 Subpart M, ANSI Z59.1-2007, and ANSI A10.32-2012 regulations. **Compatible roof pitch: flat**

All fasteners, equipment, and connections must be selected and deemed compatible with the Skyhook Anchor by a Competent Person. Refer to instructions for installation. Structure must withstand MINIMUM load of 5,000 lbs.

Substrate strength requirements: Wood: 3/4" CDX plywood or better; Metal: 20ga or thicker; Concrete: 2000 p.s.i. minimum

Avoid contact with sharp and abrasive edges and surfaces.

WARNING Avoid contact with all hazards, including, but not limited to, electrical shock, corrosive substances, and excessive heat.

Capacity range: 130-310 lbs., or up to 420 lbs. "see instructions (including all equipment)

Materials: Powder-coated steel. 9611 (Rev. 4)

www.guardianfall.com 6305 S. 231st St., Kent, WA 98032 1-800-466-6385

GUARDIAN
FALL PROTECTION
SkyMast Skyhook Anchor
Part #: 00315
Date of manufacture: [REDACTED]

Prior to use, read and understand all instructions provided with equipment at time of shipment from manufacturer.

Compliant with all OSHA 1910, OSHA 1926 Subpart M, ANSI Z59.1-2007, and ANSI A10.32-2012 regulations. **Compatible roof pitch: 7/12 - 3/12**

All fasteners, equipment, and connections must be selected and deemed compatible with the Skyhook Anchor by a Competent Person. Refer to instructions for installation. Structure must withstand MINIMUM load of 5,000 lbs.

Substrate strength requirements: Wood: 3/4" CDX plywood or better; Metal: 20ga or thicker; Concrete: 2000 p.s.i. minimum

Avoid contact with sharp and abrasive edges and surfaces.

WARNING Avoid contact with all hazards, including, but not limited to, electrical shock, corrosive substances, and excessive heat.

Capacity range: 130-310 lbs., or up to 420 lbs. "see instructions (including all equipment)

Materials: Powder-coated steel. 9612 (Rev. 4)

www.guardianfall.com 6305 S. 231st St., Kent, WA 98032 1-800-466-6385

GUARDIAN
FALL PROTECTION
SkyMast Skyhook Anchor
Part #: 00325
Date of manufacture: [REDACTED]

Prior to use, read and understand all instructions provided with equipment at time of shipment from manufacturer.

Compliant with all OSHA 1910, OSHA 1926 Subpart M, ANSI Z59.1-2007, and ANSI A10.32-2012 regulations. **Compatible roof pitch: 4/12 - 6/12**

All fasteners, equipment, and connections must be selected and deemed compatible with the Skyhook Anchor by a Competent Person. Refer to instructions for installation. Structure must withstand MINIMUM load of 5,000 lbs.

Substrate strength requirements: Wood: 3/4" CDX plywood or better; Metal: 20ga or thicker; Concrete: 2000 p.s.i. minimum

Avoid contact with sharp and abrasive edges and surfaces.

WARNING Avoid contact with all hazards, including, but not limited to, electrical shock, corrosive substances, and excessive heat.

Capacity range: 130-310 lbs., or up to 420 lbs. "see instructions (including all equipment)

Materials: Powder-coated steel. 9613 (Rev. 4)

www.guardianfall.com 6305 S. 231st St., Kent, WA 98032 1-800-466-6385

GUARDIAN
FALL PROTECTION
SkyMast Skyhook Anchor
Part #: 00335
Date of manufacture: [REDACTED]

Prior to use, read and understand all instructions provided with equipment at time of shipment from manufacturer.

Compliant with all OSHA 1910, OSHA 1926 Subpart M, ANSI Z59.1-2007, and ANSI A10.32-2012 regulations. **Compatible roof pitch: 7/12 - 9/12**

All fasteners, equipment, and connections must be selected and deemed compatible with the Skyhook Anchor by a Competent Person. Refer to instructions for installation. Structure must withstand MINIMUM load of 5,000 lbs.

Substrate strength requirements: Wood: 3/4" CDX plywood or better; Metal: 20ga or thicker; Concrete: 2000 p.s.i. minimum

Avoid contact with sharp and abrasive edges and surfaces.

WARNING Avoid contact with all hazards, including, but not limited to, electrical shock, corrosive substances, and excessive heat.

Capacity range: 130-310 lbs., or up to 420 lbs. "see instructions (including all equipment)

Materials: Powder-coated steel. 9614 (Rev. 4)

www.guardianfall.com 6305 S. 231st St., Kent, WA 98032 1-800-466-6385

GUARDIAN
FALL PROTECTION
SkyMast Skyhook Anchor
Part #: 00345
Date of manufacture: [REDACTED]

Prior to use, read and understand all instructions provided with equipment at time of shipment from manufacturer.

Compliant with all OSHA 1910, OSHA 1926 Subpart M, ANSI Z59.1-2007, and ANSI A10.32-2012 regulations. **Compatible roof pitch: 10/12 - 12/12**

All fasteners, equipment, and connections must be selected and deemed compatible with the Skyhook Anchor by a Competent Person. Refer to instructions for installation. Structure must withstand MINIMUM load of 5,000 lbs.

Substrate strength requirements: Wood: 3/4" CDX plywood or better; Metal: 20ga or thicker; Concrete: 2000 p.s.i. minimum

Avoid contact with sharp and abrasive edges and surfaces.

WARNING Avoid contact with all hazards, including, but not limited to, electrical shock, corrosive substances, and excessive heat.

Capacity range: 130-310 lbs., or up to 420 lbs. "see instructions (including all equipment)

Materials: Powder-coated steel. 9615 (Rev. 4)

www.guardianfall.com 6305 S. 231st St., Kent, WA 98032 1-800-466-6385

Use: must inspect prior to EACH use. Competent Person must complete formal inspection every 6 months. Competent Person to inspect and initial. Date of last use: _____ Product lifetime is indefinite as long as equipment passes pre-use and Competent Person inspections.

INSPECTION GRID	25	MONTHS												
		YR	J	F	M	A	M	J	J	A	S	O	N	D
25														
25														
25														
25														

If equipment fails inspection DO NOT REMOVE LABELS

