

WARTHOG® MAXX BELTED SIDE D-RING HARNESS



Key Features

- Flexible and Comfortable Support Waist Belt
- Break Away Lanyard Keepers
- Protected Identification Label
- Finished Webbing Ends
- Fall Indicator
- Ouick Disconnect Chest Buckle
- Tongue Buckle Legs
- · Side Positioning D-Rings
- Meets ANSI Z359.11-2014, ANSI Z359.3-2007, ANSI A10.32-12, OSHA 1926 Subpart M and OSHA 1910
- ANSI Capacity Range: 130-310 lbs.
- Materials: Polyester and Steel

The Warthog® MAXX Construction Full Body Harness is designed to help protect workers in heavy duty trades. With features like shoulder pads, additional adjustability, a padded waist belt, side positioning D-Rings, and quick disconnect chest buckle, it's easy to see why it is the most cost effective harness of its class. Like the Warthog®, the Warthog® MAXX comes standard with dual lanyard keepers, a protected identification label, is OSHA® compliant, and meets all applicable ANSI® standards.

Part #	Part Name	Weight
B2101	Warthog® MAXX Construction Belted Side D-Ring Harness (XS)	5 lbs.
B2102	Warthog® MAXX Construction Belted Side D-Ring Harness (S-M-L)	5.1 lbs.
B2103	Warthog® MAXX Construction Belted Side D-Ring Harness (XL-XXL)	5.2 lbs.
B2104	Warthog® MAXX Construction Belted Side D-Ring Harness (XXXL)	5.4 lbs.

