



# LEADING EDGE SAFETY

## TRIEX™ MOBILE FALL PROTECTION

The *ONLY* fall arrest cart with a locking engagement arm that ensures your anchor point is locked in its deepest point of penetration during a fall. The TriRex™ incorporates a streamlined design with a three-point front axle locking mechanism.

Now with an improved steering break and easy handle installation & removal.

### KEY FEATURES

- 3 workers on fall arrest
- 2 workers on fall restraint
- Made in America - manufactured to be the best quality in the industry
- Compliant with OSHA regulation 1926.502(D)
- US Patent Number: 8,240,431 B2

**AXLE-LOCK SYSTEM**—Locking the steering is as easy as pulling the lever forward. No need to worry about attaching parts, the axle handle lock comes pre-attached.

**HANDLE ATTACHMENT**—No need to struggle with handle attachment. An all new design allows for easy alignment and fastens with a snap-lock pin.



Proudly manufactured  
in the USA.



LEADINGEDGESAFETY.NET

© Leading Edge Safety, LLC.  
1345 Taney  
North Kansas City, MO 64116  
(888) 990-2990

PH: 215-335-6797

f in t www.panthereast.com





# TRIREX

## Mobile Fall Protection



www.leadingedgesafety.net  
(888) 990.2990

## TR-000-20 Single Job Box

### Dimensions

<b>Length</b>	78" without handle attached; 111" with handle attached
<b>Width</b>	48"
<b>Height</b>	53"
<b>Weight</b>	1000 LBS
<b>Tire Foot Print</b>	3" x 5"
<b>Approximate Downforce Applied</b>	16.71 PSI
<b>Approximate Weight Per Tire</b>	250.75 LBS
<b>Platform Size</b>	29" x 47"
<b>Height from Platform</b>	24"
<b>Ground Clearance</b>	5.5"
<b>Warranty</b>	Manufacturer's limited warranty covers any defect in workmanship or materials for one year from date of purchase
<b>Fall Arrest Capacity</b>	Three workers
<b>Fall Restraint Capacity</b>	Two workers
<b>Weight Carry Capacity of Trailer</b>	2000 LBS
<b>Compliance</b>	OSHA 1926.502(d) Fall Arrest Anchor

No substitute for the original-The ONLY fall arrest cart with a locking engagement arm that ensures your anchor point is locked in its deepest point of penetration during a fall. The TriRex™ incorporates a streamlined design with a three-point front axle locking mechanism. Keep your workers safe and mobile with the TriRex™. The TriRex™ meets and exceeds OSHA 1926.502 & ANSI/ASSE Z359.6-2009(D).

### Add-On Options

#### RAPTOR ALERT™

Fall warning system includes 130 decible siren and strobe light.  
RAS-000-09



#### RAPTOR RESCUE™

Fall retrieval system provides for prompt rescue of fallen workers.  
RAS-000-12



#### SLR TRAY

For upright positioning of SRL's off the roof surface..  
SLR-000-13



### Standard Job Box

<b>Dimensions</b>	47.5"w x 30"d x 24"h
<b>Capacity</b>	20 cubic ft
<b>Weight</b>	140 LBS

### Small Job Box

<b>Dimensions</b>	24"w x 30"d x 24"h
<b>Capacity</b>	12 cubic ft
<b>Weight</b>	85 LBS

### Key Features

- Streamlined Design
- Added safety features including 3 point positive locking breaks and engagement arm lock
- Support for 3 workers on fall arrest and 2 workers on fall restraint
- Flat free tires with roller bearings for ease of use
- Advanced standard options:
  - fork pockets
  - 4 corner D-Rings for hoisting and securing
- US Patent-8,240,431 B2
- Compliant with OSHA regulation 1926.502(d)



PH: 215-335-6797

f in t www.panthereast.com



# TRIEX

## Mobile Fall Protection



www.leadingedgesafety.net  
(888) 990.2990

## TR-002-20 Double Job Box (Small)

### Dimensions

<b>Length</b>	78" without handle attached; 111" with handle attached
<b>Width</b>	48"
<b>Height</b>	53"
<b>Weight</b>	1003 LBS
<b>Tire Foot Print</b>	3" x 5"
<b>Approximate Downforce Applied</b>	16.71 PSI
<b>Approximate Weight Per Tire</b>	250.75 LBS
<b>Platform Size</b>	29" x 47"
<b>Height from Platform</b>	24"
<b>Ground Clearance</b>	5.5"
<b>Warranty</b>	Manufacturer's limited warranty covers any defect in workmanship or materials for one year from date of purchase
<b>Fall Arrest Capacity</b>	Three workers
<b>Fall Restraint Capacity</b>	Two workers
<b>Weight Carry Capacity of Trailer</b>	2000 LBS
<b>Compliance</b>	OSHA 1926.502(d) Fall Arrest Anchor

No substitute for the original-The ONLY fall arrest cart with a locking engagement arm that ensures your anchor point is locked in its deepest point of penetration during a fall. The TriRex™ incorporates a streamlined design with a three-point front axle locking mechanism. Keep your workers safe and mobile with the TriRex™. The TriRex™ meets and exceeds OSHA 1926.502 & ANSI/ASSE Z359.6-2009(D).

### Add-On Options

#### RAPTOR ALERT™

Fall warning system includes 130 decible siren and strobe light.  
**RAS-000-09**



#### RAPTOR RESCUE™

Fall retrieval system provides for prompt rescue of fallen workers.  
**RAS-000-12**



#### SLR TRAY

For upright positioning of SRL's off the roof surface..  
**SLR-000-13**



### Standard Job Box

<b>Dimensions</b>	47.5"w x 30"d x 24"h
<b>Capacity</b>	20 cubic ft
<b>Weight</b>	140 LBS

### Small Job Box

<b>Dimensions</b>	24"w x 30"d x 24"h
<b>Capacity</b>	12 cubic ft
<b>Weight</b>	85 LBS

### Key Features

- Streamlined Design
- Added safety features including 3 point positive locking breaks and engagement arm lock
- Support for 3 workers on fall arrest and 2 workers on fall restraint
- Flat free tires with roller bearings for ease of use
- Advanced standard options:
  - fork pockets
  - 4 corner D-Rings for hoisting and securing
- US Patent-8,240,431 B2
- Compliant with OSHA regulation 1926.502(d)



PH: 215-335-6797

f in www.panthereast.com





# TRIEX

## Mobile Fall Protection



www.leadingedgesafety.net  
(888) 990.2990

### TR-003-20 Double Job Box (Large)

#### Dimensions

Length	78" without handle attached; 111" with handle attached
Width	48"
Height	53"
Weight	1143 LBS
Tire Foot Print	3" x 5"
Approximate Downforce Applied	16.71 PSI
Approximate Weight Per Tire	250.75 LBS
Platform Size	29" x 47"
Height from Platform	24"
Ground Clearance	5.5"
Warranty	Manufacturer's limited warranty covers any defect in workmanship or materials for one year from date of purchase
Fall Arrest Capacity	Three workers
Fall Restraint Capacity	Two workers
Weight Carry Capacity of Trailer	2000 LBS
Compliance	OSHA 1926.502(d) Fall Arrest Anchor



**Add-On Options**  
(SAME AS OTHER PAGES)

#### Standard Job Box

Dimensions	47.5"w x 30"d x 24"h
Capacity	20 cubic ft
Weight	140 LBS

#### Small Job Box

Dimensions	24"w x 30"d x 24"h
Capacity	12 cubic ft
Weight	85 LBS

#### Key Features

- Streamlined Design
- Added safety features including 3 point positive locking breaks and engagement arm lock
- Support for 3 workers on fall arrest and 2 workers on fall restraint
- Flat free tires with roller bearings for ease of use
- Advanced standard options:
  - fork pockets
  - 4 corner D-Rings for hoisting and securing
- US Patent-8,240,431 B2
- Compliant with OSHA regulation 1926.502(d)



PH: 215-335-6797

f in www.panthereast.com